## Gancio KNEW
**KNEW Toggle**

Thanks to its special low design, this toggle is frequently used for general transportation purposes in the construction industry, for instance of sheet piles. As the toggle is welded into the sling with the next size up chain link, it takes up little space and is also suitable for small sizes. We recommend using a 10 mm chain for the transportation of standing sheet piles.

Note: the Knew is welded to a WIN 10 link and dia 8 mm chain of the required length, with a terminal master link

Grazie alle dimensioni compattissime questo dispositivo viene utilizzato nel campo delle costruzioni, per esempio per la movimentazione di palancole. Il dispositivo viene fornito saldato alla catena, ingombra pochissimo ed è idoneo per passare attraverso fori piccoli.
Riferirsi alla tabella per il minimo ed il massimo foro consentito.
Per la movimentazione di palancole montate, raccomandiamo di utilizzare una catena dia 10mm di grado 10.

Nb: il dispositivo viene fornito saldato con maglia WIN 10 e catena dia 8 mm della lunghezza desiderata , completo di campanella all'estremità

| **Tipo** Type | **Portata** WLL | **Per catena** For chain | **Dimensioni** Dimensions | | | | | | | **Maglia di collegamento** Connecting link | **Peso** Weight |
|---|---|---|---|---|---|---|---|---|---|---|---|
| | **Kg** | **Ø** | **a mm** | **b mm** | **c mm** | **d1 mm** | **d min mm** | **d max mm** | **e mm** | | **Kg** |
| KNEW 8 | 2500 | 8 | 17 | 120 | 38 | 15 | 40 | 60 | 10 | WIN 10 | 0,17 |




