

## DATI TECNICI

TECHNICAL DATA

Portata Capacity	Sbraccio Arm length	Gru tipo Crane type	Paranco Kito tipo Kito hoist type	Dimensioni Dimensions								P daN	M daN
				H mm	H1 mm	B mm	Con carrello a spinta With plain trolley		Con carrello elettrico With electric trolley		D mm		
daN	m						C mm	C mm	D mm	E mm			
250 + 250	4 + 4	C2T 2B 25/ 4+4	KQ3S-SD	4000	3450	4010	415	455	865	180	1125	3000	
250 + 250	5 + 5	C2T 2B 25/ 5+5	KQ3S-SD	4000	3250	5010	415	455	1040	180	1185	3875	
250 + 250	6 + 6	C2T 2B 25/ 6+6	KQ3S-SD	4000	3250	6010	415	455	1040	180	1400	4815	
250 + 250	7 + 7	C2T 2B 25/ 7+7	KQ3S-SD	4000	3150	7010	415	455	1125	180	1435	5710	
250 + 250	8 + 8	C2T 2B 25/ 8+8	KQ3S-SD	4000	3050	8010	415	455	1300	180	1780	7080	
500 + 500	2 + 2	C2T 2B 50/ 2+2	KQ5S-SD	4000	3250	2010	430	470	610	180	1665	2840	
500 + 500	3 + 3	C2T 2B 50/ 3+3	KQ5S-SD	4000	3250	3010	430	470	865	180	1705	4180	
500 + 500	4 + 4	C2T 2B 50/ 4+4	KQ5S-SD	4000	3250	4010	430	470	955	180	1940	5720	
500 + 500	5 + 5	C2T 2B 50/ 5+5	KQ5S-SD	4000	3150	5010	430	470	1040	180	2090	7220	
500 + 500	6 + 6	C2T 2B 50/ 6+6	KQ5S-SD	4000	3050	6010	430	470	1130	180	2280	8865	
500 + 500	7 + 7	C2T 2B 50/ 7+7	KQ5S-SD	4000	3050	7010	430	470	1215	180	2395	10715	
500 + 500	8 + 8	C2T 2B 50/ 8+8	KQ5S-SD	4000	3150	8010	430	470	1390	180	2450	12385	
1000 + 1000	3 + 3	C2T 2B 100/ 3+3	KQ10S-SD	4000	3150	3010	490	525	970	190	3170	8140	
1000 + 1000	4 + 4	C2T 2B 100/ 4+4	KQ10S-SD	4000	3050	4010	490	525	1140	190	3375	10995	
1000 + 1000	5 + 5	C2T 2B 100/ 5+5	KQ10S-SD	4000	3050	5010	490	525	1190	190	3440	13680	
1000 + 1000	6 + 6	C2T 2B 100/ 6+6	KQ10S-SD	4000	3050	6010	490	525	1190	190	3515	16625	
1000 + 1000	7 + 7	C2T 2B 100/ 7+7	KQ10S-SD	4000	3050	7010	490	525	1190	190	3635	19700	

Carichi calcolati secondo UNI EN 13001.  
Loads calculated according to UNI EN 13001.

