

## Funi di acciaio a 6 trefoli


Steel wire ropes 6 strands

**ANIMA METALLICA**

STEEL CORE

### DRL 508 AR (lucida)

DRL 508 AR (ungalvanized)



#### 247 FILI

6x31WS+IWRC  
anima metallica  
crociata destra  
crociata sinistra

**Resistenza 2160 N/mm<sup>2</sup>**

#### 247 WIRES

6x31WS+IWRC  
steel core  
right regular lay  
left regular lay

**Tensile rope grade 2160 N/mm<sup>2</sup>**

| Codice<br>Code | Diametro<br>funne<br>Rope diameter<br>mm | Diametro<br>fili esterni<br>Outer wires diameter<br>mm | Peso<br>per metro<br>Weight for meter<br>kg | Carico<br>rottura minimo<br>MBL |       |
|----------------|--|--|---|---------------------------------|-------|
|                |  |  |   | kN                              | kg    |
| FLDRL18        | 18                                       | 1,16   | 1,44  | 245,00                          | 25000 |
| FLDRL20        | 20                                       | 1,28   | 1,78  | 304,00                          | 31000 |
| FLDRL22        | 22                                       | 1,40   | 2,11  | 380,00                          | 38760 |
| FLDRL24        | 24                                       | 1,54   | 2,54  | 430,00                          | 43700 |
| FLDRL26        | 26                                       | 1,66   | 2,93  | 510,00                          | 52000 |
| FLDRL28        | 28                                       | 1,80   | 3,46  | 595,00                          | 60690 |
| FLDRL30        | 30                                       | 1,92   | 3,80  | 688,00                          | 70170 |
| FLDRL32        | 32                                       | 2,00   | 4,21  | 798,00                          | 81390 |