


HYFIL 6 COMPATTATA PARALLELA PLASTIFICATA (zincata)

HYFIL 6 COMPACTED STRANDS LANG LAY PLASTIC IMPREGNATION (galvanized)



235 FILI
6xK31WS+EPIWRC
anima metallica plastificata
trefoli compattati
parallela destra
parallela sinistra
Resistenza 1960 N/mm²

235 WIRES
6xK31WS+EPIWRC
plastified steel core
compacted strands
right lang lay
left lang lay
Tensile rope grade 1960 N/mm²

Codice Code	Diametro funo Rope diameter mm	Diametro fili esterni Outer wires diameter mm	Peso per metro Weight for meter kg	Carico rottura minimo MBL	
				kN	kg
FZ636HYP16	16	1,07	1,22	209,80	21400
FZ636HYP18	18	1,21	1,55	265,69	27100
FZ636HYP20	20	1,34	1,91	327,45	33400
FZ636HYP22	22	1,48	2,31	397,06	40500
FZ636HYP24	24	1,61	2,75	472,55	48200
FZ636HYP26	26	1,74	3,23	554,90	56600
FZ636HYP28	28	1,88	3,75	643,14	65600
FZ636HYP30	30	2,01	4,31	739,22	75400
FZ636HYP32	32	2,15	4,90	840,20	85700