

Codice Code		Grandezza gancio Hook size		Dimensioni Dimensions							Cuscinetto adatto Suitable bearing	
Classe P Class P	Classe V Class V	Figura 1 Figure 1	Figura 2 Figure 2	d2 mm	l2 mm	l3 mm	l4 mm	t1 mm	t2 mm	r11 mm	Classe P Class P	Classe V Class V
540 401 PS	540 401 VS	1,6	-	30	68	-	221	40	-	3	51107	81107
540 402 PS	540 402 VS	2,5	-	36	83	-	250	50	-	3	51108	81108
540 404 PS	540 404 VS	4	-	42	93	-	282	56	-	3	51110	81110
540 405 PS	540 405 VS	5	-	45	103	-	315	62	-	3	51112	81112
540 406 PS	540 406 VS	-	6	50	-	112	375	79	4	3	51214	81214
540 408 PS	540 408 VS	-	8	56	-	122	413	85	4,5	3	51216	81216
540 410 PS	540 410 VS	-	10	64	-	135	446	95,5	5,5	3	51218	81218
540 412 PS	540 412 VS	-	12	72	-	157	505	110,5	6,5	3	51220	81220
540 416 PS	540 416 VS	-	16	80	-	170	576	120,5	7	3	51222	81222
540 420 PS	540 420 VS	-	20	90	-	187	645	128	8	3	51224	81224
540 425 PS	540 425 VS	-	25	100	-	207	716	144	10	3	51226	81226
540 432 PS	540 432 VS	-	32	110	-	232	788	159	11,5	3	51232	81232
540 440 PS	540 440 VS	-	40	125	-	257	885	177,5	13,5	3	51236	81236
540 450 PS	540 450 VS	-	50	140	-	280	969	201,5	15	5	51244	81244

- Scelta della portata secondo UNI9465-DIN15400
- Choice of the load capacities according to UNI9465-DIN15400

