

CARATTERISTICHE
SPECIFICATION

| Tipo Type | Larghezza interna Inner width mm | Larghezza esterna Outer width mm | Idonee per fasce doppio strato Suitable for 2 layer web slings mm | Idonee per anelli continui* TZE, TLX, TEX Suitable for round slings* TZE, TLX, TEX t | Idonee per anelli continui* ULEX, ULTF Suitable for round slings* ULEX, ULTF t |
|--------------|--|--|---|--|--|
| UPHD 65 | 65 | 75 | 50 | 1 - 2 - 3 | 2 - 3 - 4 |
| UPHD 75 | 75 | 85 | 60 | 4 | 5 - 6 |
| UPHD 90 | 90 | 100 | - | 5 - 6 | 8 - 10 |
| UPHD 115 | 115 | 125 | 90 | 8 - 10 | 12 - 15 - 20 |
| UPHD 125 | 125 | 135 | - | - | - |
| UPHD 145 | 145 | 155 | 120 | 12 - 15 | 25 |
| UPHD 175 | 175 | 185 | 150 | 20 - 25 | 30 - 35 - 40 |
| UPHD 220 | 220 | 230 | 180 | 30 - 35 - 40 | 50 - 60 |
| UPHD 275 | 275 | 285 | 240 | 50 - 60 | 70 - 80 - 90 |
| UPHD 335 | 335 | 345 | 300 | 70 | 100 - 120 |

* Entrambi i bracci dell'anello inseriti nella guaina.
* Both round sling legs in the sleeve.

